






Flexible pipe in which the creep of a sealing liner into the reinforcement is restricted


Numéro du brevet: FR2744511
Date de publication: 1997-08-08
Inventeur: LE NOUVEAU JOEL
Demandeur: COFLEXIP (FR)
Classification:
- internationale F16L11/08
- européenne F16L11/08D; F16L11/08H; F16L11/16
Numéro de demande FR19960001290 19960202
Numéro(s) de priorité: FR19960001290 19960202

Également publié en tant que

	WO9728393 (A1)
	EP0877888 (A1)
	US6085798 (A1)
	EP0877888 (B1)
	AU710046 (B2)

Abrégé pour **FR2744511**

A flexible pipe including at least one sealing liner (1); an assembly (3) of external reinforcements for withstanding the physical and chemical stress to which the flexible pipe is exposed, which assembly particularly comprises a reinforcement (2) resistant to the pressure of the fluid to be conveyed and consisting of non-contiguous coils (7, 8) wound around said sealing liner (1) in a predetermined direction (e); and an intermediate strip (11) arranged between the pressure-resistant reinforcement (2) and the sealing liner (1), and wound around said sealing liner in a direction parallel or opposite to the winding direction (e) of the coils of the pressure-resistant reinforcement. The intermediate strip (11) has a low modulus of stiffness in said winding direction (e) around the sealing liner, and a high strength and modulus of stiffness in a transverse direction (e') relative to said coil winding direction.



Data supplied from the esp@cenet database - Worldwide